



Product Description:

ANOVI UNIVERSAL GU10 120mm 1-Way Surface Downlight Adj. Round Matt Black

ANOVI UNIVERSAL PROFILE round matt black ceiling light 1 head. Maximum lamp power of source (not included): 6W. Cross-connect terminal block with pre-connected socket included. Protection class II, IP20, 100mm wired, H05S-K. Installation/installation method: surface-mounted. Dimensions: diameter 66mm. Fixing type: screws onto the support. Material: aluminum. Operating temperatures: -20°C/+40°C. Installation under false ceiling/under concrete-brick-slab ceiling. Adapts to your desires thanks to i

SKU Code

29301

Finish Colour

Matt Black

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Colour switchable between 2700/3000/4000K
- 500/525/600lm, up to 88lm/W
- Adjustable
- Aluminium material
- Pre-wired with 100mm of cable
- 35000hrs lifetime
- 5 year warranty

Product Specs:

Input Voltage	~230V AC	Input Frequency	50/60HZ
IP Rating	IP20	Lamp Base	GU10
Length (mm)	180	Overall Diameter (mm)	66
Height (mm)	120	Product Type	Downlights, Track Spotlights, Architectural Lighting
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

## Compliance & Approvals:

## Warranty:

This product has a warranty period of 2 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.