

JC24242EM

RadiaLED Style Slim Emergency

RadiaLED Slim Mains IP44 Ø410mm Bulkhead 32W 4000K LED White/Opal EM

Features & Benefits

- 16W, 28W and 38W CFL replacements
- · Like for like retrofit
- IK09 impact rating
- Instant start up, no warm up time











Ceiling

410

RadiaLED

General Information

Overall Dimensions

Mounting
Trade Name

Environment Indoor

Product Group LED - 3M Surface

Color Finish White

Product Shape Round

Product Range Style Slim

IK Rating IK09

Height (mm)

Diameter (mm) 410
Product Weight(kg) 1.67
Light Source LED

Light Source Features Vibrant White

Recommended Product Location Suitable for indoor use

IP Rating IP44
Origin of manufacturer China

5 Year Warranty (2 year on batteries) (See Website for terms

LED Manufacturer/Type Runlite 2835

Lighting Product Type 1 Emergency Lighting

and conditions)

Lighting Product Type 2 Ceiling Mount
Lighting Product Type 3 Wall Light

Customs Tariff code** 9405119090

Electrical

Warranty

Voltage Rating 220-240V~

Primary Running Current(Amp) 0.24

Operating Frequency Hz 50/60Hz

Secondary running current(mA) 270

Constant Current or Constant Voltage CC

Luminaire Circuit Wattage 32

Class

Output Voltage Max/Range (VDC) 100-114

Power Factor Correction 0.9

Emergency Data

Load Voltage(DC)24-54LOR % in Emergency Mode15Minimum Battery run time3

Recharge Time 24 Hours
Inverter PFC 0.88

Battery Data

Battery Specification 3.7V 2600mAH Li-ion

Battery Type Lithium-ion

Nominal Battery Current 1.1A

Charge Current 200mA NOM

Recharge Time 24 Hours

Battery Total Weight(kg) 0.2

Thermals

Operating Temperature Range °C

0 to +26

Performance Data

LED Life (Hours)* 54000

Energy Rating

This product contains a light source of energy efficiency

class G

Actual Lumen Output 2900

Lumens Per Circuit Watt 90

Standard Deviation Colour Matching - SDCM <6

Color Rendering Index 80-89

CRI: Ra **80**

Correlated Color Temperature 4000

Beam Angle ° 120

LOR (Light Output Ratio) % 100

Photometry Available Yes, on request

Construction

Primary Material Steel

Outer Diffuser Opal polycarbonate

Packaging

Quantity Per Outer Carton 6

Product Bar Code EAN-13 Number 5052544090714

Standards & Approvals

Manufactured In Accordance To BS EN 60598-2-1

CE Marked Yes


UKCA Marked Yes

Date code/Purchase order No.


Yes
WEEE Symbol
Yes

Certificate Of Conformity Available on request

Accredited Members LIA, ISO9001-2015, ISO14001-2015







*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

**JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products.

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT. Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 123 [27/10/2023]