



AMARLED5/WW

Marlo LED UGR<19 Suspended Linear - 54W Warm White



Features

Aluminium bi-directional suspended pendant suitable for commercial applications

Supplied bi-directional light output as standard (directional only option can be selected if required)

High output, high efficiency 90° lens technology offers optimum glare control and comfort for task / office applications.

Pre-wired with 2 metre cable

Adjustable suspension points c/w suspension kit

Powered by Tridonic

General Information

Lamp Type	LED
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Suspended
Lifetime (Hrs)	L80 B50 36,000
Warranty (Years)	5
CE Mark	Yes
Length (mm)	1700
Width (mm)	60

Technical Information

Wattage	54W
Lumens Delivered	4470lm
Lm/W	83lm
Beam Angle	90
CRI	Ra 90
CCT	3000K
Input	220-240V
Hertz	50/60Hz
Operating Temp	0°C to 25°C
SDCM	3
UGR	13

Datasheet generated from <https://onetimepim.com> last updated Tuesday, July 5, 2022 2:23:24 PM



AMARLED5/CW

Marlo LED UGR<19 Suspended Linear - 54W Cool White



Features

Aluminium bi-directional suspended pendant suitable for commercial applications

Supplied bi-directional light output as standard (directional only option can be selected if required)

High output, high efficiency 90° lens technology offers optimum glare control and comfort for task / office applications.

Pre-wired with 2 metre cable

Adjustable suspension points c/w suspension kit

Powered by Tridonic

General Information

Lamp Type	LED
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Suspended
Lifetime (Hrs)	L80 B50 36,000
Warranty (Years)	5
CE Mark	Yes
Length (mm)	1700
Width (mm)	60

Technical Information

Wattage	54W
Lumens Delivered	4750lm
Lm/W	88lm
Beam Angle	90
CRI	Ra 90
CCT	4000K
Input	220-240V
Hertz	50/60Hz
Operating Temp	0°C to 25°C
SDCM	3
UGR	13

Datasheet generated from <https://onetimepim.com> last updated Tuesday, July 5, 2022 2:23:24 PM