
Prism Pro Fire Rated Downlight



- IP65 dimmable LED Fire Rated Downlight suitable for residential and hospitality applications
- CCT selectable between 2700K, 3000K, 4000K and 6000K and power selectable; offering a choice of 2 outputs, in one luminaire
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Remote driver with 2x1.5mm² + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Low profile design and remote driver allows installation into shallow ceiling voids
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations
- Fully tested to meet Part C (moisture), Part E (acoustic) and
 Part L (energy) of Building Regulations
- Wide 65° beam angle for increased light distribution





Available bezel options Chrome, Satin Chrome and Black

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI		SDCM	BEAM ANGLE	CLASS	IP
220/240V	50/60Hz	0/60Hz -20°C to 35°C L70 60,000		Ra 80		6	65°	1	IP65
CODE	DESCRIPTION		WATTAGE	CCT		LUMENS		LM/W	UGR
APRIP/1	CCT Selectable		5/7W	2700K/3000K/		560lm(4000K 5	W) 110	llm(4000K 5W)	25
APRIP/1/MP1	CCT Selec	table Multipack x 10		4000K/6000K		740lm (4000K 7	'W) 105	lm (4000K 7W)	20
								* UGR Valu	e based on (4H - 8H)
CODE (ACCESSORIES)		DESCRIPTION			CODE (ACCESSORIES)			DESCRIPTION	
APRILEDPBZ/CH	Chrome Trim Bezel				APRILEDP/CP/MW		С	Converter Kit Matt White	
APRILEDPBZ/SC	Satin Chrome Trim Bezel				APRILEDP/CP/CH			Converter Kit Chrome	
APRILEDPBZ/BLK		Matt Black Trim Bezel			APRILEDP/CP/SC		Со	Converter Kit Satin Chrome	
ACFLP/3		LED Emergency Lighting Pack			APRILEDP/CP/BLK			Converter Kit Black	