

FAÇADE LIGHTS SPECIFICATION SHEET



LEDLINE 400 25x6

25x6° wall washing light bar

FEATURES

IK rating	IK02
IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	180°
Dimmable	Yes with suitable driver.
Input	700mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	1
Construction Material	Anodised aluminium
Weight	0.9kg
Maximum ambient temperature	40°C
Electric Class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Finish	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
LEDLINE 400 NW 25X6	Black	16W	4000K	25x6°	1000	63	3174
LEDLINE 400 WW 25X6	Black	16W	3000K	25x6°	750	47	2380
LEDLINE 400 27 25X6	Black	16W	2700K	25x6°	730	46	2317

WIRING INFORMATION

Cable / Flying Lead	3m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/700 3-9	220-240V	Yes	No	1	1	1
PL/IP/700 3-9	N/A	Yes	No	1	1	1
PLD UNI-DRIVE 700MA	N/A	Yes	Yes (1-10V)	2	1	1


ACCESSORIES


JB4 / JB6	Gel filled junction box
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
WCR 275 BLACK	2-core rubber cable
ULBRACKET	2-piece black anodised aluminium bracket




COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Asymmetric beam angle for distance wall wash

Robust cable for permanent use outdoors

Beam angle: 25x6°

