



ATHECO5/CW

Thunder ECO 32/47W 4000K



Features

Robust, high performance LED non-corrosive suitable for ancillary areas and industrial applications

Power selectable; offering high and low output option in each length

Twist off end cap and push fit terminals aid fast and easy installation

Supplied complete with versatile stainless steel mounting clips. Clips can be located anywhere along the spine of the luminaire

Non-Dimmable

General Information

IP Rating	IP65
IK Rating	IK08
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface
Lifetime (Hrs)	L80 54,000
Warranty (Years)	3
Length (mm)	1535
Width (mm)	64

Technical Information

Wattage	32/47W
Lumens Delivered	4250/5830lm
Lm/W	133/124lm
CRI	Ra 80
CCT	4000K
Input	220-240V
Hertz	50Hz
Operating Temp	-20°C to 40°C
SDCM	6

Datasheet generated from <https://onetimepim.com> last updated Tuesday, July 5, 2022 2:23:21 PM



ATHECO5/DL

Thunder ECO 32/47W 6500K



Features

Robust, high performance LED non-corrosive suitable for ancillary areas and industrial applications

Power selectable; offering high and low output option in each length

Twist off end cap and push fit terminals aid fast and easy installation

Supplied complete with versatile stainless steel mounting clips. Clips can be located anywhere along the spine of the luminaire

Non-Dimmable

General Information

IP Rating	IP65
IK Rating	IK08
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface
Lifetime (Hrs)	L80 54,000
Warranty (Years)	3
Length (mm)	1535
Width (mm)	64

Technical Information

Wattage	32/47W
Lumens Delivered	4050/5720lm
Lm/W	131/122lm
CRI	Ra 80
CCT	6500K
Input	220-240V
Hertz	50Hz
Operating Temp	-20°C to 40°C
SDCM	6

Datasheet generated from <https://onetimepim.com> last updated Tuesday, July 5, 2022 2:23:21 PM