




Product Description: BackLite™ 26W 600 x 600mm Panel


Uniquely lensed LED's have been engineered to ensure maximum light output and complete uniformity. Producing up to 140lm/W for outstanding energy savings, the TP(a) and true UGR19 rated backlit panel is suitable for a wide range of applications including office, education and commercial spaces.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-BLPP6060/30	26	3000	3460	134	90	White	Non Dimmable
AU-BLPP6060/40	26	4000	3640	140	90	White	Non Dimmable
AU-BLPP6060/65	26	6500	3640	140	90	White	Non Dimmable
AU-BLPP6060DA/30	26	3000	3460	134	90	White	DALI Dimmable
AU-BLPP6060DA/40	26	4000	3640	140	90	White	DALI Dimmable
AU-BLPP6060DA/65	26	6500	3640	140	90	White	DALI Dimmable
AU-BLPP6060V/30	26	3000	3460	134	90	White	1-10V Dimmable
AU-BLPP6060V/40	26	4000	3640	140	90	White	1-10V Dimmable
AU-BLPP6060V/65	26	6500	3640	140	90	White	1-10V Dimmable


Line Drawing



Polar Curve



Colour



White

Feature & Benefits

- No light guide, removing the risk of yellowing
- PMMA lenses for uniformity of light
- SDCM <5 providing consistent light colour quality
- Flicker free driver
- Power Factor > 0.9
- IP54 rated from the front
- TP(a) rated
- UGR19
- Suitable for installation in 15 and 24mm T-bar ceilings
- 5 Year Warranty
- 3 year onsite warranty (registration required) *Terms and conditions apply

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP54
Lifetime L70 (hrs)	50000hrs	Lifetime L80 (Hours)	50000hrs
IK Rating	IK02	Width (mm)	595
Length (mm)	595	Weight (Kg)	1.866
Height (mm)	27	Product Type	Panels
Operating Temp. (Min) °C	-25°C	Operating Temp. (Max) °C	40°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.