



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Indy K3 300W

Symmetrical floodlight suitable for commercial and industrial applications

Features

IK Rating	IK07
IP Rating	IP65
CSP Switchable	Single CCT
Tiltable	180°
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	L70 50,000h
CRI	CRI>80
SDCM	SDCM5
Emergency Option	No

Installation information

Install Connector Type	Flying lead
Inrush Current	IFLB1N: 30.3A 0.22ms IFLB2N: 53A 0.22ms IFLB3N: 30.3A 0.22ms
Construction Material	Die-cast aluminium (body) stainless steel 304 (bracket)
Weight	7.1kg
Ambient Temperature Range	-40°C - 40°C
SELV	No
UK Building Regulations	Part P
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
IFLB3N40	Black	300	4000K	120°	44500	138	15420
IFLB3N30	Black	300	3000K	120°	44000	147	15247

Wiring information

Cable / Flying Lead	1000mm H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required	Parallel

Accessories

PCELLKIT	Wall Mounted Photocell Kit	Sold Separately
----------	----------------------------	-----------------

Guarantee

5 years

Features & benefits

- High efficacy up to 147lm/W
- High power 300W
- Suitable for use in coastal applications
- Quick and easy installation with angle stamped brackets
- Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications
- Compatible with the PCELLKIT dusk to dawn sensor
- 6kV Surge Protection
- Asymmetrical floodlights also available in K2 product range
- Suitable for mounting upside down as an uplight

Light source energy efficiency:



Beam angle: 120°

