



DRV150700

30W CC Driver, IP20, 150-700mA, Class II SELV

Installation Information

| | |
|-----------------------------|--|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 45°C |
| Inrush Current | 5.38A 0.032ms |
| Construction Material | PC |
| UK Bathroom Zone | N/A |
| SELV | Yes |
| Electric Class (1, 2, 3) | 2 |
| Case Temperature (tc = °C) | 85 |
| DIN Rail Mount | No |
| Install Connector Type | Push-fit terminals 0,5 - 1,5mm ² |
| Connection Output | Push-fit terminals |
| UK Protection | Open Circuit, Short Circuit, Over Temperature Self Reset |
| Power Factor | 0.95 |

Electrical Characteristics

| Driver Rated Wattage | Driver Input Current | Driver Input Voltage | Drive Current | Driver Output Voltage | Power Factor |
|----------------------|----------------------|----------------------|---------------|-----------------------|--------------|
| 30W | 150mA-700mA | 220-240VAC | 150-700mA | 2.5-42VDC | 0.95 |



collingwood



30W

30W



Quick and easy installation



IP20

IP20 Perfect for indoor applications

Guarantee

Warranty 5 years

Features & benefits

- Selectable drive currents through dip switches
- 150mA, 250mA, 350mA, 500mA & 700mA Selectable Settings
- The ability to select 5 lumen levels without the use of a dimmer
- Driver to power Residential Landscape luminaires

