

LUMINAIRES - DOWNLIGHTS

EN-PLO6B

Product Description:

The Enlite range of Slim-Fit™ low profile downlights are engineered to deliver superior light output and uniformity utilising the latest edge-lit LED technology. At only 25mm deep including bracket, they are an ideal solution where ceiling voids are limited but high lumen output is required.

Product Image:




Slim-Fit™ 6W IP44 Round Low Profile LED Downlight


Product Features:

- Low cost energy saving alternative to compact fluorescent fittings
- Edge-lit low profile ideal for installations with limited recess space (25mm) and shallow ceiling voids
- Plug and play remote driver for easy installation (40mm space required)
- · Separate triac dimmable driver available
- Life not affected by frequent switching e.g. when used with occupancy controls
- IP44 rated
- 1.5kV surge protected
- 3 year warranty

Line Drawing Image



Polar Curve Image



Product Specs:

Technology	LED	LED Number of LEDs		
Luminaire Distribution	Accent	Lifetime L70 (hrs)	25000	
Input Voltage	220~240V AC Input Frequency		50/60HZ	
Dimmable	No IP Rating		IP44	
IK Rating	IKO7	Operating Env. Temp. (Min) °C	-20	
Operating Env. Temp. (Max) °C	40	Power Factor	0.8	
Overall Diameter (mm)	115	Recess Depth (mm)	50	
Cutout Diameter (mm)	105	Lamp Base	None	
Height (mm)	25	Surge Protection (kV)	1.5	
SDCM	6			

SKU Table and Ordering

SKU Code	Wattage	Lumens	Lumens/Watt	Colour	Beam Angle	Ra	SDCM
EN-PL06B/30	6	300	50	3000	110	80	6
EN-PL06B/40	6	330	55	4000	110	80	6
EN-PL06B/65	6	350	58.33	6500	110	80	6
EN-PL06BDA/30	6	300	50	3000	110	80	6
EN-PL06BDA/40	6	330	55	4000	110	80	6
EN-PLO6BDA/65	6	350	58.33	6500	110	80	6
EN-PL06BV/30	6	300	50	3000	110	80	6
EN-PL06BV/40	6	330	55	4000	110	80	6
EN-PL06BV/65	6	350	58.33	6500	110	80	6

Compliance & Approvals:

















Accessories:

SKU Image	SKU Code	Description
	EN-PLDD06	Slim-Fit™ 6W 270mA Dimmable Driver For Low Profile Downlight
£ 5	EN-PLEM	Slim-Fit™ 3 Hour Emergency Pack 6W - 12W

Warranty

This product has a warranty period of 3 Years.

Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Enlite Sales & Distribution Apex Park 6 Little Burrow Welwyn Garden City AL7 4SW United Kingdom

Tel: +44 (0) 1707 35 18 20