GROUND LIGHTS SPECIFICATION SHEET





GL007 Frosted

8W, 100lm frosted LED drive over ground / marker light

FEATURES

IK rating	IK10
IP rating	IP67
Colour flexibility	Fixed colour
Walk Over / Drive Over	Drive over (15mph maximum)
Input	220-240V 50/60Hz
LED Lifetime	70,000h L70 B10
CRI	>80Ra
	3SDCM

INSTALLATION INFORMATION

Bathroom zone	2
Inrush Current	10.7A 0.7ms
Construction Material	Stainless Steel 316 (cover ring) / Aluminium (body)
Weight	2.7Kg
Maximum ambient temperature	35°C
SELV	Yes
Electric Class (1, 2, 3)	1

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
GL007 FROSTED NW	8W	4000K	120°	101	13	43
GL007 FROSTED WW	8W	3000K	120°	96	12	33

WIRING INFORMATION

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED DRIVER

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	-	No	2	-	-

ACCESSORIES

Installation tube (included)	
JB5	Gel filled waterproof connector
WC 5-9	Quick waterproof connector



01604 495 151 collingwoodlighting.com

in /collingwoodlighting

/collingwoodlightingcollingwoodled

GUARANTEE / WARRANTY

5 year extended warranty

FEATURES & BENEFITS


Frosted effect for softer tone of light

Straight to mains

Installation tube included

10mm toughened glass, ideal for use in driveways

Beam angle: 120°



Ø185/180mm

