






01604 495 151
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

GL019

Up to 2W, 180lm mini ground light

Features

IK rating	IK07
IP rating	IP68
CSP Switchable	Fixed colour
Walk Over / Drive Over	Walk over
LED Lifetime	70,000h L70
CRI	80 Ra
SDCM	3 SDCM

Installation information

Cut Out Size	Ø 33mm
UK Bathroom Zone	0
Construction Material	Stainless steel (316)
Weight	204g
Maximum Ambient Temperature	50°C
Electric Class (1, 2, 3)	3

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED drivers

PLR/350 1-5	220-240V	Yes	No	0	1	5
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	2	1	10
PLU/700 3-9	N/A	Yes	No	1	3	9

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	

Guarantee



7 year extended warranty

Features & benefits

- 1W at 350mA or 2W at 700mA
- Coastal protected
- Low voltage groundlight
- Compact yet powerful fitting
- Shallow depth for easy installation
- Robust cable for outdoor use

Light source energy efficiency: 

Beam angles: 12° 38°





collingwood

Photometrics @ 25°C

Product code	Colour	Beam	350mA				700mA			
			W	lm	lm/W	lx @ 1m	W	lm	lm/W	lx @ 1m
GL019 F NW	4000K	38°	1W	100	100	356	2W	180	90	641
GL019 S NW	4000K	12°	1W	100	100	1715	2W	180	90	3087
GL019 F 27	2700K	38°	1W	80	80	285	2W	130	65	463
GL019 S 27	2700K	12°	1W	80	80	1372	2W	130	65	2229
GL019 F AMBER	Amber	38°	1W	20	20	88	2W	-	-	-
GL019 F BLUE	Blue	38°	1W	15	15	66	2W	25	13	110
GL019 S BLUE	Blue	12°	1W	15	15	306	2W	25	13	509
GL019 F GREEN	Green	38°	1W	80	80	352	2W	120	60	528
GL019 F RED	Red	38°	1W	35	35	154	2W	-	-	-
GL019 S RED	Red	12°	1W	35	35	712	2W	-	-	-
GL019BNBX27	2700K	12°	1W	80	80	1372	2W	130	65	2229
GL019BNBX30	3000K	12°	1W	90	90	1543	2W	150	75	2572
GL019BNBX40	4000K	12°	1W	100	100	356	2W	180	90	641
GL019BNBXBL	Blue	12°	1W	15	15	306	2W	25	13	509
GL019WBX27	2700K	38°	1W	80	80	285	2W	130	65	463
GL019WBX30	3000K	38°	1W	90	90	320	2W	150	75	534
GL019WBX40	4000K	38°	1W	100	100	356	2W	180	90	641
GL019WBXBL	Blue	38°	1W	15	15	66	2W	25	13	110
GL019AWBX27	2700K	38°	1W	80	80	285	2W	130	65	463
GL019AWBX30	3000K	38°	1W	90	90	320	2W	150	75	534
GL019ANBX27	2700K	12°	1W	80	80	1372	2W	130	65	2229
GL019ANBX30	3000K	12°	1W	90	90	1543	2W	150	75	2572

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

GL019

Discreet yet powerful, this 1W LED powered ground light is perfect for decking areas, entrance halls and pathways. Indoors or out, the IP68 black finish ground light will give a flawless performance for many years of maintenance free operation. Available in four ambient LED colours, the GL019 is the most popular ground light in the Collingwood range.