Ground lights specification sheet





GL045

8W, 610lm walk over ground light

Features

IB -1	
IP rating IP67	
CSP Switchable Fixed colour	
Tiltable No	
UGR <10	
Walk Over / Drive Over Walk over	
LED Lifetime 30,000h L70	
CRI 80 Ra	
SDCM 6 SDCM	

Installation information

Ø 120mm
2
20A 0.5ms
Stainless steel 316 (cover ring) / aluminium (body)
917g
40°C
Yes
1

Photometrics @ 25°C

Product code Fin	nish	W	Colour	Beam	lm	llm/W	lx @ 1m
GL045X30 Sto	ainless steel	8.1W	3000K	20°	610	75	2924

Wiring information

Cable / Flying Lead	160mm H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED driver

N/A (intergrated SELV driver)	220-240V	N/A	N/A	N/A	N/A	N/A

Accessories

JB5	IP68 waterproof connector	Sold Separately
WCR375BLACK	3-core rubber cable	Sold Separately
Installation Tube	Diameter: 120mm, Depth: 105mm	Included



01604 495 151 collingwoodlighting.com

collingwoodled

/collingwoodlighting

in collingwoodlighting

Guarantee

5 year extended warranty

Features & benefits

8W

Coastal protected

Mains voltage ground light

120mm cut out diameter


A narrow beam angle of 20° for a more focused light

High impact rating of IK08

High light output of 610 lumens

Low glare UGR <10

Beam angle: 20°



Ø125/117mm

