



GROUND LIGHTS SPECIFICATION SHEET




**COLLINGWOOD
LIGHTING**

01604 495 151
collingwoodlighting.com

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

GL064

4W, 65lm 4 way marker light

FEATURES

IK rating	IK10
IP rating	IP67
Colour flexibility	Fixed colour
Walk Over / Drive Over	No
Input	350mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra
SDCM	3SDCM

INSTALLATION INFORMATION

Cut Out Size	Ø 55mm
Bathroom zone	1
Efficiency	DRIVER DEPENDANT
Construction Material	Cast stainless steel (316)
Weight	1.165Kg
Maximum ambient temperature	35°C
Electric Class [1, 2, 3]	3

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Cast stainless steel for aged effect
Raised profile sending light in four directions

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	lm	lm/W	lx @ 1m
GL064	4W	3000K	65	16	9
GL064 27	4W	2700K	63	16	9

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	3/2
PLR/350 1-5	N/A	Yes	No	1	1	1
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	2	1	3/2

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors
TUBE/68	Installation tube
WCR 275 BLACK	2-core rubber cable

Beam angle:

