



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Tilt RGBW ground light

Driverless, RGBW Colour Change

Guarantee

5 years

Features

IK Rating	IK10
IP Rating	IP67
CSP Switchable	RGBW
Tiltable	25°
Walk Over / Drive Over	Drive over (15mph maximum)
LED Lifetime	L70 50,000h
CRI	CRI>80
SDCM	SDCM3

Installation information

Cut Out Size	119/147/165/193/223 mm
UK Bathroom Zone	2
Construction Material	Anodised aluminium body, 316 SS bezel
Weight	GLTM_11: 0.99kg, GLTM_14: 1.56kg, GLTM_16: 2.03kg, GLTM_19: 3.26kg ,GLTM_22: 3.98kg
Ambient Temperature Range	-25°C - 40°C
Electric Class (1, 2, 3)	3

Features & benefits

RGBW

IP67 for complete protection against ingress of dust & water

IK10 for protection against high impact

Suitable for coastal applications

Tilt angle of luminaire is adjustable, just turn knob to tilt the light distribution up to 25 degrees

Static loading capacity is 2000kg

Pre-wired with 1 meter of cable to aid the installer

TRIAC mains dimmable and DALI-2 dimmable options also available

Wiring information

Cable / Flying Lead	Pre-wired 1.0M H05RN-F, 5x1.0mm ²
Type of Wiring Required	Series

Accessories

JB5	Gel filled waterproof junction box	Sold Separately
CCDRV75DMX	Colour Change CC Driver, 8-43V 75W, DMX 4CH	Sold Separately
CCDRV75DALI	Colour Change CC Driver, 8-43V 75W, DALI-2 4CH	Sold Separately
CCDRV75RF	Colour Change CC Driver, 8-43V 75W, RF 4CH	Sold Separately
CCRFCONWIFI	Colour Change RF-WIFI Wall Control, 12VDC	Sold Separately

Light source energy efficiency:

PRODUCT CODES

	Colour / Finish	Description	Characteristic 1	Characteristic 2
GLTXS119RGBW	Stainless steel 316	Tilt XGround 119mm, 40°, RGBW-3000K	119mm cut-out	IK08
GLTXS147RGBW	Stainless steel 316	Tilt XGround 147mm, 40°, RGBW-3000K	147mm cut-out	IK08
GLTXS165RGBW	Stainless steel 316	Tilt XGround 165mm, 40°, RGBW-3000K	165mm cut-out	IK10
GLTXS193RGBW	Stainless steel 316	Tilt XGround 193mm, 40°, RGBW-3000K	193mm cut-out	IK10
GLTXS223RGBW	Stainless steel 316	Tilt XGround 223mm, 40°, RGBW-3000K	223mm cut-out	IK10

Beam angle: 40°

