

**CONSTANT VOLTAGE DRIVER 15W 24VDC IP20 NON-DIMM 200-240V INPUT
INTEGRAL**

ILDRCVA086



The Integral 15W constant voltage LED driver operates 200-240VAC input range. The LED driver provides 24V constant voltage and up to 0.625A of output current for a 15W maximum output power. Integral LED drivers deliver high reliability and efficiency $\geq 84\%$ and are fully compatible with 24V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

Details

Quick Order Code:	821852
Barcode:	5055788256694
Category:	Drivers
Range Name:	Non-Dimmable
Product Type:	Constant Voltage
Market Segment:	Commercial indoor, Residential indoor
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	103
Product Width (mm):	35.5
Product Weight (g):	16
Material:	Plastic Shell
Placement / Application:	Indoor

Electrical Data

Power Consumption (w):	15
Power Factor:	≥ 0.5
Voltage (V):	24
Input Current (A):	< 0.23
Input Voltage (V):	200-240VAC
Output Current (mA):	0-0.625
Dimming:	Non-Dimmable
Protection Function:	Short Circuit Protection, Overload Protection, Overheat Protection

EN: EN61347-1, EN61347-2-13, EN55015, EN6100-3-3,
EN6100-3-2, EN61547

LVD Certified: Yes

Light Data

Environment

EN: EN61347-1, EN61347-2-13, EN55015, EN6100-3-3,
EN6100-3-2, EN61547

LVD Certified: Yes

CE RoHS: Yes

Hg 0% (Mercury Free): Yes

IP Rating (Ingress Protection): IP20

Lowest Operating Temperature (°C): -20

Maximum Operating Temperature (°C): 45

Packaging

Package Weight (g): 67.5

Package Length (mm): 108

Package Width (mm): 38

Package Depth (mm): 21

**CONSTANT VOLTAGE DRIVER 20W 24VDC IP20 NON-DIMM 200-240V INPUT
INTEGRAL**

ILDRCVA046



The Integral 20W constant voltage LED driver operates 200-240VAC input range. The LED driver provides 24V constant voltage and up to 0.8A of output current for a 20W maximum output power. Integral LED drivers deliver high reliability and efficiency $\geq 85\%$ and are fully compatible with 24V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

Details

Quick Order Code:	121564
Barcode:	5055788238713
Category:	Drivers
Range Name:	Non-Dimmable
Product Type:	Constant Voltage
Market Segment:	Commercial indoor, Residential indoor
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	103
Product Depth (mm):	16
Product Width (mm):	35
Product Weight (g):	60
Material:	Plastic Shell
Placement / Application:	Indoor LED Lighting

Electrical Data

Power (W):	20
Power Consumption (w):	20
Power Factor:	0.5
Voltage (V):	24
Input Current (A):	0.23
Input Voltage (V):	200-240
Output Current (mA):	830
Dimming:	Non-Dimmable

Protection Function:	Short Circuit Protection, Overload Protection, Overheat Protection
EN:	EN61347-1, EN61347-2-13, EN55015, EN6100-3-3, EN6100-3-2, EN61547
LVD Certified:	Yes

Light Data

Environment

EN:	EN61347-1, EN61347-2-13, EN55015, EN6100-3-3, EN6100-3-2, EN61547
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	90
Package Length (mm):	108
Package Width (mm):	38
Package Depth (mm):	21

CONSTANT VOLTAGE DRIVER 75W 24VDC IP20 NON-DIMM 200-240V INPUT

ILDRCVA058



The Integral 75W constant voltage Super-Slim LED driver operates 200-240VAC input range. The LED driver provides 24V constant voltage and up to 3.13A of output current for a 75W maximum output power. Integral LED drivers deliver high reliability and efficiency $\geq 82\%$ and are fully compatible with 24V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

Details

Quick Order Code:	118447
Barcode:	5055788254775
Category:	Drivers
Range Name:	Non-Dimmable
Product Type:	Constant Voltage
Market Segment:	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	159
Product Depth (mm):	18
Product Width (mm):	57.8
Product Weight (g):	150
Material:	Plastic Shell
Placement / Application:	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

Electrical Data

Power Consumption (w):	75
Power Factor:	0.9
Voltage (V):	24
Input Current (A):	0.5
Input Voltage (V):	200-240
Output Current (mA):	3130

Dimming:	Non-Dimmable
Electric Current:	AC
Protection Function:	Short Circuit Protection, Overload Protection, Overheat Protection
EN:	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
LVD Certified:	Yes

Light Data

Environment

EN:	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	160
Package Length (mm):	180
Package Width (mm):	60
Package Depth (mm):	20

CONSTANT VOLTAGE DRIVER 100W 24VDC IP20 NON-DIMM 200-240V INPUT

ILDRCVA059



The Integral 100W constant voltage Super-Slim LED driver operates 200-240VAC input range. The LED driver provides 24V constant voltage and up to 4.17A of output current for a 100W maximum output power. Integral LED drivers deliver high reliability and efficiency $\geq 82\%$ and are fully compatible with 24V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

Details

Quick Order Code:	574630
Barcode:	5055788254782
Category:	Drivers
Range Name:	Non-Dimmable
Product Type:	Constant Voltage
Market Segment:	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	164
Product Depth (mm):	16.8
Product Width (mm):	56.4
Product Weight (g):	195
Material:	Plastic Shell
Placement / Application:	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

Electrical Data

Power Consumption (w):	100
Power Factor:	0.9
Voltage (V):	24
Input Current (A):	0.5
Input Voltage (V):	200-240
Output Current (mA):	4170

Dimming:	Non-Dimmable
Electric Current:	AC
Protection Function:	Short Circuit Protection, Overload Protection, Overheat Protection
EN:	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
LVD Certified:	Yes

Light Data

Environment

EN:	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	205
Package Length (mm):	167
Package Width (mm):	58
Package Depth (mm):	19

CONSTANT VOLTAGE DRIVER 150W 24VDC IP20 NON-DIMM 200-240V INPUT

ILDRCVA060



The Integral 150W constant voltage Super-Slim LED driver operates 200-240VAC input range. The LED driver provides 24V constant voltage and up to 6.25A of output current for a 150W maximum output power. Integral LED drivers deliver high reliability and efficiency $\geq 82\%$ and are fully compatible with 24V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

Details

Quick Order Code:	425949
Barcode:	5055788254799
Category:	Drivers
Range Name:	Non-Dimmable
Product Type:	Constant Voltage
Market Segment:	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	177
Product Depth (mm):	17.2
Product Width (mm):	56.4
Product Weight (g):	200
Material:	Plastic Shell
Placement / Application:	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

Electrical Data

Power Consumption (w):	150
Power Factor:	0.9
Voltage (V):	24
Input Current (A):	0.85
Input Voltage (V):	200-240
Output Current (mA):	6250

Dimming:	Non-Dimmable
Electric Current:	AC
Protection Function:	Short Circuit Protection, Overload Protection, Overheat Protection
EN:	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
LVD Certified:	Yes

Light Data

Environment

EN:	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	210
Package Length (mm):	180
Package Width (mm):	60
Package Depth (mm):	20