

**CONSTANT VOLTAGE LONG & SLIM DRIVER 30W 24VDC IP20 NON-DIMM  
180-264V INPUT**

ILDRCVA065



The Integral 30W constant voltage Long & Slim LED driver operates 200-240VAC input range. The LED driver provides 24V constant voltage and up to 1.25A of output current for a 30W maximum output power. Integral LED drivers deliver high reliability and efficiency  $\geq 82\%$  and are fully compatible with 24V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

**Details**

<b>Quick Order Code:</b>	352960
<b>Barcode:</b>	5055788254812
<b>Category:</b>	Drivers
<b>Range Name:</b>	Non-Dimmable
<b>Product Type:</b>	Constant Voltage
<b>Market Segment:</b>	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	251
<b>Product Depth (mm):</b>	16
<b>Product Width (mm):</b>	30
<b>Product Weight (g):</b>	135
<b>Material:</b>	Plastic Shell
<b>Placement / Application:</b>	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

**Electrical Data**

<b>Power Consumption (w):</b>	30
<b>Power Factor:</b>	0.9
<b>Voltage (V):</b>	24
<b>Input Current (A):</b>	0.22
<b>Input Voltage (V):</b>	200-240

<b>Output Current (mA):</b>	1250
<b>Dimming:</b>	Non-Dimmable
<b>Electric Current:</b>	AC
<b>Protection Function:</b>	Short Circuit Protection, Overload Protection, Overheat Protection
<b>EN:</b>	EN61000-3-2, EN55015, EN61547
<b>LVD Certified:</b>	Yes

## Light Data

## Environment

<b>EN:</b>	EN61000-3-2, EN55015, EN61547
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45

## Packaging

<b>Package Weight (g):</b>	140
<b>Package Length (mm):</b>	263
<b>Package Width (mm):</b>	38
<b>Package Depth (mm):</b>	22

**CONSTANT VOLTAGE LONG & SLIM DRIVER 45W 24VDC IP20 NON-DIMM  
180-264V INPUT**

ILDRCVA066



The Integral 45W constant voltage Long & Slim LED driver operates 200-240VAC input range. The LED driver provides 24V constant voltage and up to 1.87A of output current for a 45W maximum output power. Integral LED drivers deliver high reliability and efficiency  $\geq 82\%$  and are fully compatible with 24V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

**Details**

<b>Quick Order Code:</b>	239151
<b>Barcode:</b>	5055788254836
<b>Category:</b>	Drivers
<b>Range Name:</b>	Non-Dimmable
<b>Product Type:</b>	Constant Voltage
<b>Market Segment:</b>	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	251
<b>Product Depth (mm):</b>	16
<b>Product Width (mm):</b>	23.6
<b>Product Weight (g):</b>	135
<b>Material:</b>	Plastic Shell
<b>Placement / Application:</b>	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

**Electrical Data**

<b>Power Consumption (w):</b>	45
<b>Power Factor:</b>	0.9
<b>Voltage (V):</b>	24
<b>Input Current (A):</b>	0.3
<b>Input Voltage (V):</b>	200-240

<b>Output Current (mA):</b>	1870
<b>Dimming:</b>	Non-Dimmable
<b>Electric Current:</b>	AC
<b>Protection Function:</b>	Short Circuit Protection, Overload Protection, Overheat Protection
<b>EN:</b>	EN61000-3-2, EN55015, EN61547
<b>LVD Certified:</b>	Yes

## Light Data

## Environment

<b>EN:</b>	EN61000-3-2, EN55015, EN61547
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45

## Packaging

<b>Package Weight (g):</b>	140
<b>Package Length (mm):</b>	263
<b>Package Width (mm):</b>	38
<b>Package Depth (mm):</b>	22

**CONSTANT VOLTAGE LONG & SLIM DRIVER 75W 24VDC IP20 NON-DIMM  
180-264V INPUT**

ILDRCVA067



The Integral 75W constant voltage Long & Slim LED driver operates 200-240VAC input range. The LED driver provides 24V constant voltage and up to 3.125A of output current for a 75W maximum output power. Integral LED drivers deliver high reliability and efficiency  $\geq 82\%$  and are fully compatible with 24V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

**Details**

<b>Quick Order Code:</b>	955614
<b>Barcode:</b>	5055788254874
<b>Category:</b>	Drivers
<b>Range Name:</b>	Non-Dimmable
<b>Product Type:</b>	Constant Voltage
<b>Market Segment:</b>	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	304.6
<b>Product Depth (mm):</b>	16.7
<b>Product Width (mm):</b>	30
<b>Product Weight (g):</b>	168
<b>Material:</b>	Plastic Shell
<b>Placement / Application:</b>	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

**Electrical Data**

<b>Power Consumption (w):</b>	75
<b>Power Factor:</b>	0.9
<b>Voltage (V):</b>	24
<b>Input Current (A):</b>	0.6
<b>Input Voltage (V):</b>	200-240

<b>Output Current (mA):</b>	3125
<b>Dimming:</b>	Non-Dimmable
<b>Electric Current:</b>	AC
<b>Protection Function:</b>	Short Circuit Protection, Overload Protection, Overheat Protection
<b>EN:</b>	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
<b>LVD Certified:</b>	Yes

## Light Data

## Environment


<b>EN:</b>	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45

## Packaging

<b>Package Weight (g):</b>	180
<b>Package Length (mm):</b>	325
<b>Package Width (mm):</b>	36
<b>Package Depth (mm):</b>	23

**CONSTANT VOLTAGE LONG & SLIM DRIVER 100W 24VDC IP20 NON-DIMM  
180-264V INPUT**

ILDRCVA068



The Integral 100W constant voltage Long & Slim LED driver operates 200-240VAC input range. The LED driver provides 24V constant voltage and up to 4.17A of output current for a 100W maximum output power. Integral LED drivers deliver high reliability and efficiency >= 82% and are fully compatible with 24V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

**Details**

<b>Quick Order Code:</b>	371575
<b>Barcode:</b>	5055788254898
<b>Category:</b>	Drivers
<b>Range Name:</b>	Non-Dimmable
<b>Product Type:</b>	Constant Voltage
<b>Market Segment:</b>	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	304.6
<b>Product Depth (mm):</b>	18
<b>Product Width (mm):</b>	30
<b>Product Weight (g):</b>	196
<b>Material:</b>	Plastic Shell
<b>Placement / Application:</b>	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

**Electrical Data**

<b>Power Consumption (w):</b>	100
<b>Power Factor:</b>	0.9
<b>Voltage (V):</b>	24
<b>Input Current (A):</b>	1
<b>Input Voltage (V):</b>	200-240

<b>Output Current (mA):</b>	4170
<b>Dimming:</b>	Non-Dimmable
<b>Electric Current:</b>	AC
<b>Protection Function:</b>	Short Circuit Protection, Overload Protection, Overheat Protection
<b>EN:</b>	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
<b>LVD Certified:</b>	Yes

## Light Data

## Environment

<b>EN:</b>	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45

## Packaging

<b>Package Weight (g):</b>	200
<b>Package Length (mm):</b>	330
<b>Package Width (mm):</b>	40
<b>Package Depth (mm):</b>	25