

**CONSTANT VOLTAGE LONG & SLIM DRIVER 30W 12VDC IP20 NON-DIMM
180-264V INPUT**

ILDRCVA061



The Integral 30W constant voltage Long & Slim LED driver operates 200-240VAC input range. The LED driver provides 12V constant voltage and up to 2.5A of output current for a 30W maximum output power. Integral LED drivers deliver high reliability and efficiency $\geq 82\%$ and are fully compatible with 12V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

Details

Quick Order Code:	386247
Barcode:	5055788254805
Category:	Drivers
Range Name:	Non-Dimmable
Product Type:	Constant Voltage
Market Segment:	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	251
Product Depth (mm):	16
Product Width (mm):	30
Product Weight (g):	130
Material:	Plastic Shell
Placement / Application:	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

Electrical Data

Power Consumption (w):	30
Power Factor:	0.9
Voltage (V):	12
Input Current (A):	0.22
Input Voltage (V):	200-240

Output Current (mA):	2500
Dimming:	Non-Dimmable
Electric Current:	AC
Protection Function:	Short Circuit Protection, Overload Protection, Overheat Protection
EN:	EN61000-3-2, EN55015, EN61547
LVD Certified:	Yes

Light Data

Environment

EN:	EN61000-3-2, EN55015, EN61547
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	140
Package Length (mm):	263
Package Width (mm):	38
Package Depth (mm):	22

**CONSTANT VOLTAGE LONG & SLIM DRIVER 45W 12VDC IP20 NON-DIMM
180-264V INPUT**

ILDRCVA062



The Integral 45W constant voltage Long & Slim LED driver operates 200-240VAC input range. The LED driver provides 12V constant voltage and up to 3.75A of output current for a 45W maximum output power. Integral LED drivers deliver high reliability and efficiency $\geq 82\%$ and are fully compatible with 12V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

Details

Quick Order Code:	641615
Barcode:	5055788254829
Category:	Drivers
Range Name:	Non-Dimmable
Product Type:	Constant Voltage
Market Segment:	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	251
Product Depth (mm):	16
Product Width (mm):	30
Product Weight (g):	130
Material:	Plastic Shell
Placement / Application:	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

Electrical Data

Power Consumption (w):	45
Power Factor:	0.9
Voltage (V):	12
Input Current (A):	0.3
Input Voltage (V):	200-240

Output Current (mA):	3750
Dimming:	Non-Dimmable
Electric Current:	AC
Protection Function:	Short Circuit Protection, Overload Protection, Overheat Protection
EN:	EN61000-3-2, EN55015, EN61547
LVD Certified:	Yes

Light Data

Environment

EN:	EN61000-3-2, EN55015, EN61547
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	140
Package Length (mm):	263
Package Width (mm):	38
Package Depth (mm):	22

**CONSTANT VOLTAGE LONG & SLIM DRIVER 75W 12VDC IP20 NON-DIMM
180-264V INPUT**

ILDRCVA063



The Integral 75W constant voltage Long & Slim LED driver operates 200-240VAC input range. The LED driver provides 12V constant voltage and up to 6.25A of output current for a 75W maximum output power. Integral LED drivers deliver high reliability and efficiency $\geq 82\%$ and are fully compatible with 12V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

Details

Quick Order Code:	429754
Barcode:	5055788254867
Category:	Drivers
Range Name:	Non-Dimmable
Product Type:	Constant Voltage
Market Segment:	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	304.6
Product Depth (mm):	16.7
Product Width (mm):	30
Product Weight (g):	168
Material:	Plastic Shell
Placement / Application:	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

Electrical Data

Power Consumption (w):	75
Power Factor:	0.9
Voltage (V):	12
Input Current (A):	0.6
Input Voltage (V):	200-240

Output Current (mA):	6250
Dimming:	Non-Dimmable
Electric Current:	AC
Protection Function:	Short Circuit Protection, Overload Protection, Overheat Protection
EN:	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
LVD Certified:	Yes

Light Data

Environment


EN:	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6, EN61547
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	180
Package Length (mm):	326
Package Width (mm):	36
Package Depth (mm):	30

**CONSTANT VOLTAGE LONG & SLIM DRIVER 100W 12VDC IP20 NON-DIMM
180-264V INPUT**

ILDRCVA064



The Integral 100W constant voltage Long & Slim LED driver operates 200-240VAC input range. The LED driver provides 12V constant voltage and up to 8.33A of output current for a 100W maximum output power. Integral LED drivers deliver high reliability and efficiency $\geq 82\%$ and are fully compatible with 12V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

Details

Quick Order Code:	556154
Barcode:	5055788254881
Category:	Drivers
Range Name:	Non-Dimmable
Product Type:	Constant Voltage
Market Segment:	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	304.6
Product Depth (mm):	18
Product Width (mm):	30
Product Weight (g):	196
Material:	Plastic Shell
Placement / Application:	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

Electrical Data

Power Consumption (w):	100
Power Factor:	0.9
Voltage (V):	12
Input Current (A):	0.7
Input Voltage (V):	200-240

Output Current (mA):	8330
Dimming:	Non-Dimmable
Electric Current:	AC
Protection Function:	Short Circuit Protection, Overload Protection, Overheat Protection
EN:	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6-8-11, EN61547
LVD Certified:	Yes

Light Data

Environment

EN:	EN61000-3-2, EN55015, EN61000-4-2-3-4-5-6-8-11, EN61547
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	200
Package Length (mm):	330
Package Width (mm):	40
Package Depth (mm):	25