


**COMPACT ECO LINEAR 65W 10075LM 4000K 155LM/W 120 BEAM  
NON-DIMM INTEGRAL**

ILHBL080

**Details**

<b>Quick Order Code:</b>	759040
<b>Barcode:</b>	5055788260998
<b>Category:</b>	Luminaires
<b>Range Name:</b>	Compact Eco
<b>Type:</b>	Linear
<b>Market Segment:</b>	Commercial indoor, Industrial indoor
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	625
<b>Product Weight (g):</b>	1800
<b>Optic:</b>	Polycarbonate
<b>Material:</b>	Aluminium, Polycarbonate
<b>Construction:</b>	Aluminium heat-sink and driver case
<b>Bulb or Luminaire Shape:</b>	Linear
<b>Luminaire Fixing:</b>	Surface or Suspended
<b>Mounting Type:</b>	Surface or Suspended
<b>Placement / Application:</b>	Indoor, Commercial and Industrial

**Electrical Data**

<b>Power Consumption (w):</b>	65
<b>Power Factor:</b>	0.9
<b>Wattage equivalent (W):</b>	100
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>EN:</b>	EN-60598, EN61000, EN61547, EN55015, IEC62321
<b>LVD Certified:</b>	Yes

**Light Data**

	10075
<b>Luminous Flux in Lumens (lm):</b>	155
<b>Luminous efficacy (lm/W):</b>	4000
<b>Correlated Colour Temperature (CCT) (K):</b>	Cool White
<b>Colour Temperature Name:</b>	120
<b>Beam Angle:</b>	80
<b>Colour Rendering Index (CRI):</b>	Yes
<b>Instant on (Less than 1 second):</b>	2835
<b>LED Size (mm):</b>	Surface mounted device (SMD)
<b>LED Type:</b>	50000
<b>Lifetime (hours):</b>	15000
<b>Switching Cycles:</b>	

## Environment


<b>EN:</b>	EN-60598, EN61000, EN61547, EN55015, IEC62321
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>EU Luminaire:</b>	L
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IK Rating (Impact Protection):</b>	IK08
<b>IP Rating (Ingress Protection):</b>	IP65
<b>Lowest Operating Temperature (°C):</b>	-10
<b>Maximum Operating Temperature (°C):</b>	40

## Packaging

<b>Package Weight (g):</b>	2200
<b>Package Length (mm):</b>	650
<b>Package Width (mm):</b>	130
<b>Package Depth (mm):</b>	66

**COMPACT ECO LINEAR 65W 10075LM 5000K 155LM/W 120 BEAM  
NON-DIMM INTEGRAL**

ILHBL081

**Details**

<b>Quick Order Code:</b>	922946
<b>Barcode:</b>	5055788261001
<b>Category:</b>	Luminaires
<b>Range Name:</b>	Compact Eco
<b>Type:</b>	Linear
<b>Market Segment:</b>	Commercial indoor, Industrial indoor
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	625
<b>Product Weight (g):</b>	1800
<b>Optic:</b>	Polycarbonate
<b>Material:</b>	Aluminium, Polycarbonate
<b>Construction:</b>	Aluminium heat-sink and driver case
<b>Bulb or Luminaire Shape:</b>	Linear
<b>Luminaire Fixing:</b>	Surface or Suspended
<b>Mounting Type:</b>	Surface or Suspended
<b>Placement / Application:</b>	Indoor, Commercial and Industrial

**Electrical Data**

<b>Power Consumption (w):</b>	65
<b>Power Factor:</b>	0.9
<b>Wattage equivalent (W):</b>	100
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>EN:</b>	EN-60598, EN61000, EN61547, EN55015, IEC62321
<b>LVD Certified:</b>	Yes

**Light Data**

	10075
<b>Luminous Flux in Lumens (lm):</b>	155
<b>Luminous efficacy (lm/W):</b>	5000
<b>Correlated Colour Temperature (CCT) (K):</b>	Daylight
<b>Colour Temperature Name:</b>	120
<b>Beam Angle:</b>	80
<b>Colour Rendering Index (CRI):</b>	Yes
<b>Instant on (Less than 1 second):</b>	2835
<b>LED Size (mm):</b>	Surface mounted device (SMD)
<b>LED Type:</b>	50000
<b>Lifetime (hours):</b>	15000
<b>Switching Cycles:</b>	

## Environment

<b>EN:</b>	EN-60598, EN61000, EN61547, EN55015, IEC62321
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>EU Luminaire:</b>	L
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IK Rating (Impact Protection):</b>	IK08
<b>IP Rating (Ingress Protection):</b>	IP65
<b>Lowest Operating Temperature (°C):</b>	-10
<b>Maximum Operating Temperature (°C):</b>	40

## Packaging

<b>Package Weight (g):</b>	2200
<b>Package Length (mm):</b>	650
<b>Package Width (mm):</b>	130
<b>Package Depth (mm):</b>	66

**COMPACT ECO LINEAR 120W 18600LM 4000K 155LM/W 120 BEAM  
NON-DIMM INTEGRAL**

ILHBL090

**Details**

<b>Quick Order Code:</b>	245737
<b>Barcode:</b>	5055788261018
<b>Category:</b>	Luminaires
<b>Range Name:</b>	Compact Eco
<b>Type:</b>	Linear
<b>Market Segment:</b>	Commercial indoor, Industrial indoor
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	1220
<b>Product Weight (g):</b>	4000
<b>Optic:</b>	Polycarbonate
<b>Material:</b>	Aluminium, Polycarbonate
<b>Construction:</b>	Aluminium heat-sink and driver case
<b>Bulb or Luminaire Shape:</b>	Linear
<b>Luminaire Fixing:</b>	Surface or Suspended
<b>Mounting Type:</b>	Surface or Suspended
<b>Placement / Application:</b>	Indoor, Commercial and Industrial

**Electrical Data**

<b>Power Consumption (w):</b>	120
<b>Power Factor:</b>	0.9
<b>Wattage equivalent (W):</b>	186
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>EN:</b>	EN-60598, EN61000, EN61547, EN55015, IEC62321
<b>LVD Certified:</b>	Yes

**Light Data**

	18600
<b>Luminous Flux in Lumens (lm):</b>	155
<b>Luminous efficacy (lm/W):</b>	4000
<b>Correlated Colour Temperature (CCT) (K):</b>	Cool White
<b>Colour Temperature Name:</b>	120
<b>Beam Angle:</b>	80
<b>Colour Rendering Index (CRI):</b>	Yes
<b>Instant on (Less than 1 second):</b>	2835
<b>LED Size (mm):</b>	Surface mounted device (SMD)
<b>LED Type:</b>	50000
<b>Lifetime (hours):</b>	15000
<b>Switching Cycles:</b>	

## Environment

<b>EN:</b>	EN-60598, EN61000, EN61547, EN55015, IEC62321
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>EU Luminaire:</b>	L
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IK Rating (Impact Protection):</b>	IK08
<b>IP Rating (Ingress Protection):</b>	IP65
<b>Lowest Operating Temperature (°C):</b>	-10
<b>Maximum Operating Temperature (°C):</b>	40

## Packaging

<b>Package Weight (g):</b>	4400
<b>Package Length (mm):</b>	1270
<b>Package Width (mm):</b>	130
<b>Package Depth (mm):</b>	66

**COMPACT ECO LINEAR 120W 18600LM 5000K 155LM/W 120 BEAM  
NON-DIMM INTEGRAL**

ILHBL091

**Details**

<b>Quick Order Code:</b>	208742
<b>Barcode:</b>	5055788261025
<b>Category:</b>	Luminaires
<b>Range Name:</b>	Compact Eco
<b>Type:</b>	Linear
<b>Market Segment:</b>	Commercial indoor, Industrial indoor
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	1220
<b>Product Weight (g):</b>	4000
<b>Optic:</b>	Polycarbonate
<b>Material:</b>	Aluminium, Polycarbonate
<b>Construction:</b>	Aluminium heat-sink and driver case
<b>Bulb or Luminaire Shape:</b>	Linear
<b>Luminaire Fixing:</b>	Surface or Suspended
<b>Mounting Type:</b>	Surface or Suspended
<b>Placement / Application:</b>	Indoor, Commercial and Industrial

**Electrical Data**

<b>Power Consumption (w):</b>	120
<b>Power Factor:</b>	0.9
<b>Wattage equivalent (W):</b>	186
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>EN:</b>	EN-60598, EN61000, EN61547, EN55015, IEC62321
<b>LVD Certified:</b>	Yes

**Light Data**

	18600
<b>Luminous Flux in Lumens (lm):</b>	155
<b>Luminous efficacy (lm/W):</b>	5000
<b>Correlated Colour Temperature (CCT) (K):</b>	Daylight
<b>Colour Temperature Name:</b>	120
<b>Beam Angle:</b>	80
<b>Colour Rendering Index (CRI):</b>	Yes
<b>Instant on (Less than 1 second):</b>	2835
<b>LED Size (mm):</b>	Surface mounted device (SMD)
<b>LED Type:</b>	50000
<b>Lifetime (hours):</b>	15000
<b>Switching Cycles:</b>	

## Environment

<b>EN:</b>	EN-60598, EN61000, EN61547, EN55015, IEC62321
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>EU Luminaire:</b>	L
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IK Rating (Impact Protection):</b>	IK08
<b>IP Rating (Ingress Protection):</b>	IP65
<b>Lowest Operating Temperature (°C):</b>	-10
<b>Maximum Operating Temperature (°C):</b>	40

## Packaging

<b>Package Weight (g):</b>	4400
<b>Package Length (mm):</b>	1270
<b>Package Width (mm):</b>	130
<b>Package Depth (mm):</b>	66