DECORATIVE WALL LIGHTS + UNDERSHELF LIGHTING

SPECIFICATION SHEET



ML02

Decorative LED mini light

FEATURES

IP rating	IP68
Colour flexibility	Fixed colour
Dimmable	Yes With suitable driver
Input	350mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra or -
SDCM	3SDCM

INSTALLATION INFORMATION

Cut Out Size	Ø 26mm
Bathroom zone	0
Construction Material	Stainless steel (316)
Weight	50g
Maximum ambient temperature	35°C
Electric Class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	lm	lm/W	lx @ 1m	
ML02 NW	1W	4000K	35	35	4	
ML02 WW	1W	3000K	24	24	3	
ML02 27	1W	2700K	23	23	3	
ML02 AMBER	1W	Amber	-		-	
ML02 BLUE	1W	Blue	-		-	
ML02 GREEN	1W	Green	-		-	
ML02 RED	1W	Red	-		-	

WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm² red & black PTFE)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PLR/350 1-5	220-240V	Yes	No	Hors volume	1	5
PLD UNI-DRIVE 350MA	220-240V	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

CR135	PTFE cable
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
UY2 CONNECTOR	Quick waterproof connector



01604 495 151 collingwoodlighting.com

in /collingwoodlighting

f /collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Great for guidance lighting

Can be used in interior and exterior applications

Small & discreet decorative LED light

Raised profile creates diffused glow effect on surrounding surface

Beam angle:



