

MULTI-FIT DOWNLIGHT 65-205MM CUTOUT 1440LM 18W 3000K NON-DIMM 80LM/W WHITE

ILD205-65G007



The downlight is supplied with configurable brackets and clips allowing for installation in a cut-out from 65-205mm as well as having a surface mount installation option. Visible flicker is eliminated with the integrated driver and a frosted diffuser provides uniform light.

Details

Quick Order Code:	532268
Barcode:	5055788253037
Category:	Downlights
Range Name:	Multi-Fit
Product Type:	LED Downlights
Product Body Finish:	Matt white
Market Segment:	Commercial indoor
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Depth (mm):	22
Product Weight (g):	405
Optic:	TP(b) rated Opal diffuser
Material:	Aluminium, PS, PC
Overall diameter (mm):	230
Construction:	Die cast Aluminium body, PS sheet diffuser
Cut Out Diameter (mm):	65-205
Luminaire Fixing:	Recess or surface mounted
Placement / Application:	Indoor, General Lighting

Electrical Data

Power (W):	18
Power Consumption (w):	18
Power Factor:	0.5
Wattage equivalent (W):	26
Dimming:	Non-Dimmable
Driver Included:	Integrated


Electric Current: AC
EN: EN-60598
LVD Certified: Yes

Light Data

Luminous Flux in Lumens (lm): 1440
Luminous efficacy (lm/W): 80
Correlated Colour Temperature (CCT) (K): 3000
Colour Temperature: 3000K - Warm White
Colour Temperature Name: Warm White
Beam Angle: 110
Colour Rendering Index (CRI): 80
Frequency Range (Hz): 50/60
LED Type: Surface mounted device (SMD)
Lifetime (hours): 30000
Switching Cycles: 15000

Environment

EN: EN-60598
LVD Certified: Yes
CE RoHS: Yes
New Energy Rating: F
Hg 0% (Mercury Free): Yes
IP Rating (Ingress Protection): IP20
Lowest Operating Temperature (°C): -10
Maximum Operating Temperature (°C): 40



Packaging

Package Weight (g): 500
Package Length (mm): 275
Package Width (mm): 239
Package Depth (mm): 36

Portal.integral-led.com