G9 BULB 300LM 2.7W 4000K DIMMABLE 300 BEAM INTEGRAL

ILG9DC014



This Integral LED G9 lamp offers a high lumen output in 4000K. At 3W this smooth dimming capsule lamp is highly efficient compared to the halogen lamps they are designed to replace. Ideal for pendant fittings and accent lighting in domestic, hospitality and retail applications.

Details

Barcode: Quick Order Code: Category: Banga Name:	5055788260509 745854 Lamps G9
Range Name: Product Type:	G9
Market Segment:	Commercial indoor, Residential indoor
Warranty (Years):	2
CE RoHS:	Yes
Physical Data	
Product Length (mm):	52
Product Width (mm):	16
Product Weight (g):	8.5
Base Term:	G9
Bulb Base:	G9
Construction:	Plastic heat-sink, Injection moulded diffuser
Globe Finish:	Clear
Bulb Fixing:	Pendant, Wall, Desktop
Bulb or Luminaire Shape:	Cylindrical
Placement / Application:	Indoor, General Lighting

Electrical Data

Power (W):	2.7
Power Consumption (W) :	2.7
Power Factor:	0.4
Voltage Range (v):	220-240
Wattage equivalent (W):	28
Amperage (mA):	16
Dimming:	Dimmable with compatible dimmers


Driver IC Manufacturer:	Bright Power Semiconductor
Driver Included:	Yes
Electric Current:	AC
EN:	EN-62560
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (Im): Luminous efficacy (Im/W):	300 111
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature:	4000K - Cool White
Colour Temperature Name:	Cool White
Beam Angle:	300
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Type:	SMD
Lifetime (hours):	15000
Switching Cycles:	50000


Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
New Energy Rating:	Е
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45



Packaging

Package Weight (g): Package Length (mm): Package Width (mm):



15 Portal.int@gral-led.com 20

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

54 36000

Portal.integral-led.com