

LinearPacCWS™



Colour & Wattage Switchable Anti-Corrosives



- Colour switchable between 3000K/4000K/6500K
- Wattage switchable for 2ft, 4ft, 5ft, 6ft variants
- Delivers up to 180lm/W
- Plug and play module accessories to convert to Emergency, Emergency Self Test and Microwave Sensor with Corridor function
- Side drill out entry points up to 25mm
- Pre-drilled cable entry points on the back and ends, suitable for 20mm conduit
- Detachable 4 way loop in/loop out terminal block
- BESA mounting points on the back
- 304 stainless steel fixing clips
- DALI-2 converter pack available

3000K 4000K 6500K	2ft 7W 9W 12W 14W	4ft 14W 18W 24W 28W	5ft 18W 24W 30W 36W	6ft 27W 35W 45W 54W	CE	DALI-2 PUSH
UK CA	IP66	IK10	CRI 80	L2 Compliant		

Technical Specifications

- Supply Voltage: 220-240 AC
- Lifespan: L70 50,000hrs
- Operating Temperature: -20°C / 40°C
- Body: Polycarbonate
- Diffuser: Opal Polycarbonate
- Warranty: 5 Years (3 Years On-Site)

Cat No.	Type	Watts (W)	Colour Temp. (K)	Lumens (lm)	Lm/W	Beam (°)	Size (mm)	Size (ft)
AU-ANT600CWS	Non Dim	7 / 9 / 12 / 14	3000 / 4000 / 6500	1260 - 2520	180	120	670 x 96 x 78	2
AU-ANT1200CWS	Non Dim	14 / 18 / 24 / 28	3000 / 4000 / 6500	2520 - 5050	180	120	1270 x 96 x 78	4
AU-ANT1500CWS	Non Dim	18 / 24 / 30 / 36	3000 / 4000 / 6500	3240 - 6480	180	120	1570 x 96 x 78	5
AU-ANT1800CWS	Non Dim	27 / 35 / 45 / 54	3000 / 4000 / 6500	4860 - 9720	180	120	1870 x 96 x 78	6
AU-ANTDA1	230V 14W DALI 2 Driver for AU-ANT600CWS							
AU-ANTDA2	230V 36W DALI 2 Driver for AU-ANT1200CWS & AU-ANT1500CWS							
AU-ANTDA3	230V 54W DALI 2 Driver for AU-ANT1800CWS							
EN-ANTEM2	3h Emergency Pack for AU-ANT____CWS							
EN-ANTEMST2	3h Self-Test Emergency Pack for AU-ANT____CWS							
EN-ANTMSC2	Microwave Corridor Sensor for AU-ANT____CWS							

All lumen values based on 4000K