




## NUMINOS® S CW

**PHASE, Surface-mounted ceiling light, 2700 K, 8 Watt, trailing edge, 60°, matt black**

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® S CW, PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Deckenaufbauleuchte The luminaire impresses with a luminous flux of 950 lm and an impressive efficiency of 118.75 lm/W. Their colour temperature of 2700 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



## TECHNICAL DATA

Item no.	1004100
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	128
Primary nominal voltage	220-240AC50/60 Hz
Secondary power / voltage	200
Safety class	I
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	128
Number of luminaires at LS C16A	128
Level of inrush current	10 A
Duration of inrush current	50 µs
Lumen	950 lm
Colour temperature	2700 Kelvin
Beam angle	60 °
Color	matt black

## Light Source

1411525	
---------	---

<b>CRI</b>	90
<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Length</b>	16.2 cm
<b>Height</b>	14.5 cm
<b>Diameter</b>	6.5 cm
<b>Net weight</b>	0.577 kg
<b>Gross weight</b>	0.883 kg
<b>BIG WHITE Page</b>	337