

POND LIGHTS SPECIFICATION SHEET



UL010

Universal LED light

FEATURES

IP rating	IP68
Colour flexibility	Fixed colour
Tilttable	360°
Rotation angle	360°
Dimmable	Yes with suitable driver
Input	700mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra or -
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	0
Construction Material	Stainless steel (316)
Weight	500g
Maximum ambient temperature	35°C
Electric Class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
UL010 NW	3W	4000K	18°	119	40	648
UL010 WW	3W	3000K	18°	95	32	411
UL010 27	3W	2700K	18°	92	31	399
UL010 BL	3W	Blue	18°	-	-	-
UL010 A WW	3W	3000K	18°	95	32	411
UL010 A 27	3W	2700K	18°	92	31	399

WIRING INFORMATION

Cable / Flying Lead	3m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/700 3-9	220-240V	Yes	No	1	3	9
PLD UNI-DRIVE 700mA	N/A	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

JB2 / JB4	Waterproof junction box / Gel filled waterproof connector
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
WCR 275 BLACK	2-core rubber cable



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

/collingwoodlighting

/collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Complete with wall fixings

Robust cable for use outdoors

Tilt & rotate for adjusting light

Long lifetime of 70,000hrs

Beam angle: 18°

