



POND LIGHTS SPECIFICATION SHEET




**COLLINGWOOD
LIGHTING**

01604 495 151
collingwoodlighting.com

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

UL010RGBW

Colour change LED light (5W max.)

FEATURES

IP rating	IP67
Colour flexibility	RGBW
Tilttable	360°
Rotation angle	360°
Input	350mA
LED Lifetime	50,000h L50 B50
CRI	>80Ra

INSTALLATION INFORMATION

Bathroom zone	1
Construction Material	Stainless steel (316)
Weight	700g
Maximum ambient temperature	35°C
Electric Class (1, 2, 3)	3

GUARANTEE / WARRANTY

5 year extended warranty

FEATURES & BENEFITS

Complete with wall fixings for easy installation

Can rotate and be angled to direct light

Separate white LED for permanent use

Full RGBW colour range

Compatible with a large range of controllers

Marine grade stainless steel for use in outdoor and indoor environments

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
UL010RGBW	1.1	White	40°	50	45	101
UL010RGBW	1	Red	40°	38	38	75
UL010RGBW	1.1	Green	40°	63	57	124
UL010RGBW	1.1	Blue	40°	11	8	17

WIRING INFORMATION

Cable / Flying Lead	2x 1m CR575RGBW (outside diameter: 7.4mm)
Type of Wiring Required	Series

LED DRIVER

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PR3011	N/A	Yes	Yes	1	1	6

ACCESSORIES

JB7	5-pole IP68 inline connector
CR575RGBW	5-core PVC cable

Beam angle: 40°

