

FAÇADE LIGHTS SPECIFICATION SHEET



LEDLINE MAINS 400 25x6°

25x6° straight to mains wall washing light bar

FEATURES

IK rating	IK02
IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	180°
Input	220-240V 50/60Hz
LED Lifetime	70,000h L70 B10
CRI	>80Ra
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	2
Inrush Current	2.1A 0.1ms
Efficiency	80
Construction Material	Anodised aluminium
Weight	1.4kg
Maximum ambient temperature	35°C
SELV	Yes
Electric Class [1, 2, 3]	1

PHOTOMETRICS @ 25°C

Product code	Finish	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
ULM346M40	Black	19W	4000K	25x6°	940	50	3191
ULM346M30	Black	19W	3000K	25x6°	880	46	2987
ULM346M27	Black	19W	2700K	25x6°	860	45	2919

WIRING INFORMATION

Cable / Flying Lead	3m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED DRIVER

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	N/A	No	2	N/A	N/A

ACCESSORIES

ULBRACKET	2-piece black anodised aluminium bracket
-----------	--



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

/collingwoodlighting

/collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Asymmetric beam angle for distance wall wash

Mains driver built-in for quick installation

Robust cable for permanent use outdoors

Beam angles: C0/C180 C90/C270

