



WL95 Versa

CCT Colour & Wattage Switchable Bulkhead with plug-in Versabox accessories

Features

IP rating	IP65
CSP Switchable	Switchable CCT
Sensor Option	Microwave + Photocell options
Dimmable Option	Yes (DALI-2)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Manual, Self & DALI-2 options
IK rating	IK09

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	0.6 - 0.9kg
Inrush Current	16A 0.42ms
Construction Material	ABS Housing (RAL9003 or 9005), Anti-UV Diffuser, 850°, RG1
UK Bathroom Zone	2
Electric Class (1, 2, 3)	2
Install Connector Type	Push-fit terminal, loop-in/loop-out
Mounting Options	Ceiling & wall

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy
WL95W2NCS	White	250mm On-Off	115°	5W	3000K	700	140	
					4000K	750	150	
					6000K	750	150	
				6.5W	3000K	950	146	
					4000K	1000	154	
					6000K	1000	154	
				8W	3000K	1200	150	
					4000K	1250	156	
					6000K	1250	156	
WL95W3NCS	White	300mm On-Off	115°	10W	3000K	1450	145	
					4000K	1500	150	
					6000K	1500	150	
				15W	3000K	2100	140	
					4000K	2200	147	
					6000K	2200	147	
				20W	3000K	2800	140	
					4000K	3000	150	
					6000K	3000	150	
WL95W2DCS	White	250mm DALI-2	115°	5W	3000K	700	140	
					4000K	750	150	
					6000K	750	150	
				6.5W	3000K	950	146	
					4000K	1000	154	
					6000K	1000	154	
				8W	3000K	1200	150	
					4000K	1250	156	
					6000K	1250	156	
WL95W3DCS	White	300mm DALI-2	115°	10W	3000K	1450	140	
					4000K	1500	150	
					6000K	1500	150	
				15W	3000K	2100	140	
					4000K	2200	147	
					6000K	2200	147	
				20W	3000K	2800	140	
					4000K	3000	150	
					6000K	3000	150	
WL95B2NCS	Black	250mm On-Off	115°	5W	3000K	700	140	

C
collingwood



CCT switchable between 3000K, 4000K & 6000K



Wattage switchable options from 5W to 20W



IK09 for impact protection



Guarantee

Warranty	5 years
Battery Warranty	5 years
On-Site Warranty	2 years

Features & benefits

- IP65 suitable for use outside under a canopy
- Slim depth of just 80mm
- Ultra efficient up to 154 Llm/W for fast paybacks
- 4-way conduit entry points
- Detachable terminal block for convenient wiring
- Modular design for tool-less installation
- Versabox plug and play kit range to accommodate project requirements

Beam angle: 115°



					4000K	750	150	
					6000K	750	150	
					3000K	950	146	
					4000K	1000	154	
					6000K	1000	154	
					3000K	1200	150	
					4000K	1250	156	
					6000K	1250	156	
					3000K	1450	145	
					4000K	1500	150	
					6000K	1500	150	
					3000K	2100	140	
WL95B3NCS	Black	300mm On-Off	115°		4000K	2200	147	A t G C
					6000K	2200	147	
					3000K	2800	140	
					4000K	3000	150	
					6000K	3000	150	
					3000K	700	140	
					4000K	750	150	
					6000K	750	150	
					3000K	950	146	
					4000K	1000	154	
					6000K	1000	154	
					3000K	1200	150	
WL95B2DCS	Black	250mm DALI-2	115°		4000K	1250	156	A t G C
					6000K	1250	156	
					3000K	1450	140	
					4000K	1500	150	
					6000K	1500	150	
					3000K	2100	140	
WL95B3DCS	Black	300mm DALI-2	115°		4000K	2200	147	A t G C
					6000K	2200	147	
					3000K	2800	140	
					4000K	3000	150	
					6000K	3000	150	
					3000K	700	140	



WL95 Versa is the ultimate bulkhead, with CCT adjustable from warm 3000K to bright 6000K and wattage options ranging from 5W to 20W, all packed in a slim, impact-resistant (IK09) and weatherproof (IP65) design. Plus with high efficiency of up to 154lm/W. This bulkhead offers easy installation with 4-way conduit entry, detachable terminal block, and tool-less modular design, and is compatible with Versabox plug-and-play kits for ultimate project customization.

Wiring Information

Cable / Flying Lead	Push-fit terminals, 2.5mm² max, loop-in/loop-out.
Type of Wiring Required	Parallel

Accessories

WLKITMANEM	Manual Test Emergency plug-in Versabox, 250lm	Sold Separately
WLKITSELFEM	Self Test Emergency plug-in Versabox, 250lm	Sold Separately
WLKITPC	Photocell plug-in Versabox	Sold Separately
WLKITMWS	Microwave Sensor on/off plug-in Versabox	Sold Separately
WLKITMWSDIM	Coming Soon	Sold Separately
WL95BEW	White Eyelid Accessory (300mm only)	Sold Separately
WL95BE	Black Eyelid Accessory (300mm only)	Sold Separately

Beam angle: 115°

