

## FN-DI10

| Project      | Comments    |
|--------------|-------------|
| Fixture Type | Prepared By |

#### **Product Description:**

Performance - that's what the Uni-Fit™ range of commercial downlights stands for. Featuring ThermoTec™ technology, integrated driver and high quality LED chips to deliver serious lumen performance. The Uni-Fit™ range is the ideal cost effective solution for new or existing installations where traditional compact fluorescent downlights need upgrading to more efficient LED technology.

## Product Image:



#### **Product Features:**

- Multiple sizes and wattages available to suit all new and retrofit installation lighting requirements
- ThermoTec™ technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- · Compact integrated driver allows for easy installation
- Life not affected by frequent switching e.g. when used with occupancy controls
- · Pre-wired with 500mm 2-core cable
- · 1.5kV surge protection
- · 3 year warranty

#### **Product Specs:**

| Input Voltage   | 220~240V AC       |
|-----------------|-------------------|
| Input Frequency | 50/60Hz           |
| Power Factor    | 0.5               |
| Dimmable        | No                |
| Dimensions      | 120mm x 70mm (RD) |
| Number of LEDs  | 30                |

### Compliance & Approvals:











## SKU Table and Ordering

| Cat. No.   | Color | lm.   | Wattage | Lumens/Watt | Quantity |
|------------|-------|-------|---------|-------------|----------|
| EN-DL10/40 | 4000K | 710lm | 10W     | 71          | 1        |
| EN-DL10/30 | 3000K | 700lm | 10W     | 70          |          |

#### Warranty:

This product has a warranty period of 3 Years from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, and removal of the Q.C. date label; installation in an improper working environment or installation not according to the current edition of the National Electric Code. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

### **UK Enlite Sales**

16 Alban Park Hatfield Road St. Albans AL4 0JJ

United Kingdom

Tel: +44 (0) 1727 83 66 11 Fax: +44 (0) 1727 83 66 22

### **UK Enlite Distribution**

Apex Park 6 Little Burrow Welwyn Garden City AL7 4SW

United Kingdom



## FN-DI15

| roject | Comments |
|--------|----------|
|--------|----------|

Fixture Type Prepared By Prepared By

#### **Product Description:**

Performance - that's what the Uni-Fit™ range of commercial downlights stands for. Featuring ThermoTec™ technology, integrated driver and high quality LED chips to deliver serious lumen performance. The Uni-Fit™ range is the ideal cost effective solution for new or existing installations where traditional compact fluorescent downlights need upgrading to more efficient LED technology.

## Product Image:



#### **Product Features:**

- Multiple sizes and wattages available to suit all new and retrofit installation lighting requirements
- ThermoTec<sup>™</sup> technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- · Compact integrated driver allows for easy installation
- Life not affected by frequent switching e.g. when used with occupancy controls
- · Pre-wired with 500mm 2-core cable
- · 1.5kV surge protection
- · 3 year warranty

## **Product Specs:**

| Input Voltage   | 220~240V AC       |
|-----------------|-------------------|
| Input Frequency | 50/60Hz           |
| Power Factor    | 0.9               |
| Dimmable        | No                |
| Dimensions      | 150mm x 70mm (RD) |
| Number of LEDs  | 40                |

## Compliance & Approvals:











## SKU Table and Ordering

| Cat. No.   | Color | 1m     | Wattage | Lumens/Watt | Quantity |
|------------|-------|--------|---------|-------------|----------|
| EN-DL15/40 | 4000K | 1100lm | 15W     | 73.33       |          |
| EN-DL15/30 | 3000K | 1075lm | 15W     | 71.67       |          |

#### Warranty:

This product has a warranty period of 3 Years from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, and removal of the Q.C. date label; installation in an improper working environment or installation not according to the current edition of the National Electric Code. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

### **UK Enlite Sales**

16 Alban Park Hatfield Road St. Albans AL4 0JJ

United Kingdom

Tel: +44 (0) 1727 83 66 11 Fax: +44 (0) 1727 83 66 22

### **UK Enlite Distribution**

Apex Park 6 Little Burrow Welwyn Garden City AL7 4SW

United Kingdom



## FN-D123

| Project      | Comments    |
|--------------|-------------|
| Fivture Type | Prenared Ry |

#### **Product Description:**

Performance - that's what the Uni-Fit™ range of commercial downlights stands for. Featuring ThermoTec™ technology, integrated driver and high quality LED chips to deliver serious lumen performance. The Uni-Fit™ range is the ideal cost effective solution for new or existing installations where traditional compact fluorescent downlights need upgrading to more efficient LED technology.

## Product Image:



#### **Product Features:**

- Multiple sizes and wattages available to suit all new and retrofit installation lighting requirements
- ThermoTec<sup>™</sup> technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- · Compact integrated driver allows for easy installation
- Life not affected by frequent switching e.g. when used with occupancy controls
- . Pre-wired with 500mm 2-core cable
- · 1.5kV surge protection
- · 3 year warranty

## **Product Specs:**

| Input Voltage   | 220~240V AC       |
|-----------------|-------------------|
| Input Frequency | 50/60Hz           |
| Power Factor    | 0.9               |
| Dimmable        | No                |
| Dimensions      | 200mm x 70mm (RD) |
| Number of LEDs  | 60                |

## Compliance & Approvals:











## ✓ RoHs

### SKU Table and Ordering

| Cat. No.   | Color | lm     | Wattage | Lumens/Watt | Quantity |
|------------|-------|--------|---------|-------------|----------|
| EN-DL23/64 | 6400K | 1850lm | 23W     | 80.43       |          |
| EN-DL23/40 | 4000K | 1800lm | 23W     | 78.26       |          |
| EN-DL23/30 | 3000K | 1750lm | 23W     | 76.09       |          |

## Warranty:

This product has a warranty period of 3 Years from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, and removal of the Q.C. date label; installation in an improper working environment or installation not according to the current edition of the National Electric Code. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

### **UK Enlite Sales**

16 Alban Park Hatfield Road St. Albans AL4 0JJ

United Kingdom

Tel: +44 (0) 1727 83 66 11 Fax: +44 (0) 1727 83 66 22

### **UK Enlite Distribution**

Apex Park 6 Little Burrow Welwyn Garden City AL7 4SW

United Kingdom



## FN-DISO

| Project      | Comments    |
|--------------|-------------|
| Fixture Type | Prepared By |

#### **Product Description:**

Performance - that's what the Uni-Fit™ range of commercial downlights stands for. Featuring ThermoTec™ technology, integrated driver and high quality LED chips to deliver serious lumen performance. The Uni-Fit™ range is the ideal cost effective solution for new or existing installations where traditional compact fluorescent downlights need upgrading to more efficient LED technology.

## Product Image:



#### **Product Features:**

- Multiple sizes and wattages available to suit all new and retrofit installation lighting requirements
- ThermoTec<sup>™</sup> technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- · Compact integrated driver allows for easy installation
- Life not affected by frequent switching e.g. when used with occupancy controls
- · Pre-wired with 500mm 2-core cable
- · 1.5kV surge protection
- · 3 year warranty

# Product Specs:

| Input Voltage   | 220~240V AC       |
|-----------------|-------------------|
| Input Frequency | 50/60Hz           |
| Power Factor    | 0.9               |
| Dimmable        | No                |
| Dimensions      | 230mm x 70mm (RD) |
| Number of LEDs  | 80                |

### Compliance & Approvals:

#### SKU Table and Ordering

| Cat. No.   | Color | Im     | Wattage | Lumens/Watt | Quantity |
|------------|-------|--------|---------|-------------|----------|
| EN-DL30/64 | 6400K | 2300lm | 30W     | 76.67       |          |
| EN-DL30/30 | 3000K | 2200lm | 30W     | 73.33       |          |
| EN-DL30/40 | 4000K | 2250lm | 30W     | 75          |          |

#### Warranty:

This product has a warranty period of 3 Years from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, and removal of the Q.C. date label; installation in an improper working environment or installation not according to the current edition of the National Electric Code. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

### **UK Enlite Sales**

16 Alban Park Hatfield Road St. Albans AL4 0JJ

United Kingdom

Tel: +44 (0) 1727 83 66 11 Fax: +44 (0) 1727 83 66 22

### **UK Enlite Distribution**

Apex Park 6 Little Burrow Welwyn Garden City AL7 4SW

United Kingdom