

Aurora Enlite MPRO Integrated LED Downlights Fire Rated



Product Code: MPRO*
Stock Qty:



Product Description

Aurora MPRO integrated LED downlights that have set a new standard for high performance lighting products. Fire rated, dimmable, IP65 and insulation cover-able, this LED downlight has it all! Also included is the Aurora FastRFix wiring connector which helps to speed up installation times and makes wiring easier.

Available in 3 finishes that include matt white, polished chrome and satin nickel, also available in 2700K, 3000K and 4000K colour temperatures. The Aurora MPro has a light output of 560-640 lumens, 7W energy consumption and wide 60 degree beam angle. With a life expectancy of 40,000 hours and 5 year guarantee, the Aurora MPro is a premium quality recessed downlight at an affordable price. Our prices include a die cast aluminium bezel which is usually an additional item.

Key Features

- Three finish options:
 - Matt white
 - Polished chrome
 - Satin nickel
- Colour temperatures & Lumens:
 - Extra warm 2700K - 560 lms
 - Warm white 3000K - 600 lms
 - Cool white 4000K - 640 lms
- Colour rendering index: 80 CRI
- Dimmable as standard with an LED compatible dimmer switch such as Hamilton LEDStat
- Beam angle: 60 degrees
- Wattage: 7W and comparable a 50W halogen
- Fully integrated LED downlight that includes everything you need.
- Position: Fixed
- IP Rating: IP65 suitable for bathroom zones 1 and 2.
- Part L 1 and L2 Compliant.
- Fire rated: fully fire rated 30, 60 and 90-minute fire rated ceilings.
- Double Insulated, no earth required.
- FastRFix wiring connector included
- Insulation cover-able
- Power factor: 0.85
- Material: Die cast aluminium bezel which is included in the price.
- Life expectancy: 40,000 hours.
- Voltage: Mains voltage 240V - No additional LED driver required
- Manufacturer: Aurora Lighting
- 5 Year guarantee

The flip down driver design reduces the height to just 47mm. This allows the MPro to be fitted into shallow ceiling voids while still maintaining its status as an insulation cover-able downlight.

M-Pro Fixed Position



Product Specification

Specifications

Beam Angle (Degrees)	60 Degrees
CRI	80 Ra
Cap Type	Integrated LED
Colour Temperature	
Dimensions	Located Below Specifications Table
Dimmable	Yes
Downlight Type	Bathroom (IP65)
Finish	
Fire Rated	Yes
GTIN	5055155404505
IP Rating	IP65
Incandescent Equivalent	50 W
Insulation Coverable	Yes
Life Expectancy	70,000 Hours
Lighting Technology	LED
Lumens	560 Lumens
Manufacturer	Aurora Lighting
Material	Die-Cast Aluminium
Product Types	LED Downlight
Series	Aurora MPRO
Sku	MPRO*
Voltage	230V AC
Warranty	7 Years
Wattage	6 W